



CN 802

Carbon / Nitrogen Analyzer

Elemental Analyzer for a Wide Range
of Applications



CN 802 Carbon / Nitrogen Analyzer

The CN 802 combustion elemental analyzer is a versatile, cloud-enabled and fully automatic solution for carbon and nitrogen determination in a wide range of applications. The CN 802 offers high performance on both solid and liquid samples, working in accordance to international standards such as AOAC, AACC, ASBC, ISO, DIN, IFFO, OIV, ASTM, EPA.

RAPID C/N DETERMINATION

The CN 802 performs analysis of both carbon and nitrogen in just 3-5 minutes. The quick start and sleeping mode ensures fast operation set up with possibility of leak test per zone.

FLEXIBLE

Fully automatic determination of TC, TOC and TIC (after acidification), TN and Carbon/Nitrogen Ratio on solid and liquid samples.

PRECISE

The NDIR (Non Dispersive Infrared) detector and LoGas™ TCD (Thermal Conductivity Detector) designed by VELP guarantee unmatched precision and unrivaled LOD.

EFFICIENT

The fully automatic and reliable combustion method of CN 802 together with DriStep™ water trap guarantees moderate cost. The 30-positions disc autosampler expandable with extra 3 discs ensures maximum productivity and uptime.

VERSATILE

The CN 802 works with solid, liquid and doughy samples of up to 1 gram. Seamless carrier gas selection between Helium and Argon without hardware changes and with no memory effect.

SMART & SAFE

The CN 802 is easy to use thanks to the user-friendly CNSoft™ software which is equipped with maximum safety control of the instrument. VELP Ermes connection will deliver a new user experience and smart workflows.



CARBON DETECTOR

NDIR - NON DISPERSIVE INFRARED DETECTOR


- Selective detector reading only Carbon content
- Maintenance free
- High Accuracy and Precision
- LOD: 0,01 mgC

NITROGEN DETECTOR

TCD – THERMAL CONDUCTIVITY DETECTOR


- Low gas consumption
- No reference gas required
- Long life span
- LOD: 0.001 mgN (He) – 0.01 mgN (Ar)

CN 802 Analysis Process



- **CF** (Combustion Reactor) Allows complete combustion at 1030 °C in order to convert all of the sample into its elemental substances.
- **WT1** (Physical Water Trap) The maintenance-free DriStep™ cooler permits 99% of water to be removed.
- **RF** (Reduction Reactor) Enables the elimination of unwanted compounds and oxygen, transforming NO_x into N₂.
- **WT2** (Chemical Water Trap) Eliminates the residual water.
- **NDIR** (Non Dispersive Infrared Detector) Accurately measures the CO₂ concentration that the instrument is able to convert in carbon quantity.
- **CO₂** (CO₂ Regenerating Adsorbers) Used to get rid of all the CO₂. Auto-regenerating, maintenance-free system.
- **TCD** (Innovative TCD) LoGas™ determines nitrogen content without the need for a reference gas. Maintenance-free.

VELP ERMES CONNECTION




Connect the CN 802 to the exclusive VELP Ermes Cloud Platform to improve your laboratory experience. The VELP Ermes Cloud platform connection will unburden you from tedious tasks, improving your lab productivity.

- Real time monitor and control of the instrument from PC, smartphone and tablet whenever you want, wherever you are
- Immediate alert and notification with the possibility to stop the instrument for maximum safety
- Regular software updates will guarantee the best performance and new features with just one-click

ermes enabled

CNSoft™ Software

The CNSoft™ software is the powerful VEP solution that controls and operates the CN 802 analyzer. The CNSoft™ comes with a user-friendly interface that displays all relevant information at a glance: results, database and instrument conditions. It is possible to choose from a rich library of pre-installed methods and create customized ones.




1 BEFORE THE ANALYSIS

- Create or choose a calibration curve for C and N
- Fill in the required data (sample name, analysis type, weight...)
- Select a method and calibration curve

2 DURING THE ANALYSIS

- Monitor of the working parameters
- Realtime graph of C and N peaks
- Immediate readout of the results in mg and % of C and N, % protein



3 AFTER THE ANALYSIS

- Multiple data comparison in graph
- Data export in .xls, .txt and .csv to PC or LIMS
- Create, print and download reports of single or multiple analysis
- If necessary set the instrument in Stand-by mode or Sleeping mode
- Short statistical analysis in one click

APPLICATIONS AND METHODS

SOILS

TOTAL N: ISO 13878
TOTAL C - TOC: ISO 10694

SOILS IMPROVERS AND GROWING MEDIA

TOTAL N: EN 13654-2

SEDIMENTS

TOTAL N - TOTAL C: EPA Method 440.0

SLUDGE, TREATED BIOWASTE, SOIL AND WASTE

TOC: EN 15936

PETROLEUM PRODUCTS AND LUBRICANTS

TOTAL N - TOTAL C: ASTM Method D5291

SOLID MINERAL FUELS

TOTAL N - TOTAL C: ISO 29541

SOLID BIOFUELS

TOTAL N - TOTAL C: ISO16948

SLUDGE, TREATED BIOWASTE AND SOIL

TOTAL N: EN 16168

COAL AND COKE

TOTAL N - TOTAL C: ASTM Method D5373

FERTILIZERS

TOTAL N: AOAC 993.13

CARBON BLACK

TOTAL C: ASTM D 7633

WATER

TOC- DOC: EN 1484

WATER

TOC - DOC: ISO 8245

DRINKING, SURFACE, AND SALINE WATERS

TOC: EPA 415.1

DOMESTIC AND INDUSTRIAL WASTE

TOC: EPA 415.1

WATER FOR PHARMACEUTICAL USE

TOC: European pharmacopoeia 9th edition 2.2.44,
and USP chapter <643>

OPTIONAL ACCESSORIES

1000 analyses kit	A00000194
2000 analyses kit	A00000270
4000 analyses kit	A00000271
Disc 2 for Autosampler	A00000199
Disc 3 for Autosampler	A00000200
Disc 4 for Autosampler	A00000201
Pre-packed combustion reactor	A00000158
Pre-packed reduction reactor	A00000226
Quartz reactor tube	A00000162
Metal reactor tube	A00000321
Cleaning kit for metallic ash collector	A00000353
Ceramic ash collector	A00000198
Metallic ash collector	A00000322
Quartz ash collector	A00000161
Anhydron, 454g	A00000225
Super-Absorbent Powder, 10g	A00000317
Quartz wool, 50g	A00000154
Vcopper High Reduction Efficiency, 470g	A00000240
Copper oxide, 50g	A00000157
Velcatalyst with inert layer, 36g	A00000320
EDTA Certified, 100 gr	A00000149
Rice Flour, 30g	A00000235
Tin Foil Cups, 150pcs	A00000153
Tin Foils 50x50mm, 450 pcs	A00000260
Mold for tin foils 50x50mm	A00000262
Tin foil cup closing device	A00000217
Kit for TOC/sample preparation	TA00000378
Silver Foil 35x35mm, 100 pcs	A00000371
High temperature sealing grease	A00000236
IQ/OQ/PQ CN Manual	A00000370
VELP Ermes 1 Year Connection	E00010012
VELP Ermes 3 Year Connection	E00010036

GLP Good Laboratory Practice

AOAC	AACC	ASBC
ISO	DIN	IFFO
OIV	ASTM	EPA

INSTRUMENT - CODE

CN 802


230 V / 50-60 Hz

F30800090

SUPPLIED WITH



A00000193
Start-up kit



40001065
Autosampler
with disc 1



40002622
CNSoft™
Software



40001693
USB cable for
PC, 5m



10003926
RS232 Cable
for balance

The CN 802 is supplied with all necessary parts to perform up to 1000* analyses (inclusive of catalysts, copper, quartz wool, reagents and seals). In addition it contains chemicals and small consumables spares for maintenance.

Use Genuine VELP consumables and accessories to get the best performance from your CN 802



FIELDS OF APPLICATION

The CN 802 is extremely versatile, being suitable for carbon and nitrogen determination in several kinds of sample, in accordance with official AOAC, AACC, ASBC, ISO, ASTM, EPA, DIN and OIV methods.

AGRONOMY INDUSTRY



ENVIRONMENTAL INDUSTRY



PHARMACEUTICAL AND CHEMICAL INDUSTRY



TECHNICAL DATA

	CN 802
METHOD OF ANALYSIS	Combustion method
DETECTOR	N = TCD (Thermal Conductivity Detector) C = NDIR (Non Dispersive Infrared Detector)
CARRIER GAS	Helium and Argon
SAMPLE WEIGHT	Up to 1 g
NITROGEN MEASURING RANGE	ppm - 200 mgN
CARBON MEASURING RANGE	ppm - 150 mgC
ANALISIS TIME	3-5 min
AUTOSAMPLER CAPACITY	Up to 4 discs, 30 positions each
AUTOSAMPLER TYPE	Pneumatic
REPRODUCIBILITY (RSD)	< 0.5% for EDTA standards approx. 100 mg
RECOVERY	> 99.5%
NITROGEN DETECTION LIMIT	0.001 mgN (He); 0.01 mgN (Ar);
CARBON DETECTION LIMIT	0.01 mgC
COMBUSTION TEMPERATURE	1030 °C / 1886 °F
HELIUM (He) / ARGON (Ar)	Purity 99.999% (grade 5.0)
OXYGEN (O ₂)	Purity 99.999% (grade 5.0)
CARRIER GAS PRESSURE	2 bar
OXYGEN (O ₂) PRESSURE	2 bar
CONNECTIVITY	Cloud via LAN or Wi-Fi
INTERFACES	USB, RS232, VELP Ermes Cloud Platform
POWER	1400 W
POWER SUPPLY	230 V / 50 - 60 Hz
WEIGHT	54 kg 119 lb
DIMENSIONS (WxHxD) (including autosampler)	655 x 690 x 410 mm 25.8 x 27.2 x 16.1 in



SERVICE & SUPPORT

VELP Scientifica products are designed by our engineers to resist years of laboratory use.

Our products are manufactured with premium materials to guarantee the best performance with maximum safety.

According to our experience, a proper and regular maintenance is necessary to ensure the highest performance of analytical instrument. VELP Service Department and VELP Official Partners are always ready to offer you maintenance and service support tailored to your needs.

GET THE SUPPORT YOU NEED CHOOSING THE OPTIONS:

- Installation
- Preventive Maintenance
- Help-desk and Remote support
- Technical Assistance
- Analytical Support
- Calibration Certification



We reserve the right to make technical alterations
We do not assume liability for errors in printing, typing or transmission

VELP Official Partner

DESIGNED AND MANUFACTURED IN ITALY



ITALY - HQ
Via Stazione 16
20865 Usmate (MB) Italy
Tel. +39 039 628811
velpitalia@velp.com

INDIA
velpindia@velp.com

USA
155 Keyland Court, Bohemia
NY 11716 - U.S.
Tel. +1 631 573 6002
velpusa@velp.com

CHINA
Xinlong Rd Building 28, Lane 1333
Shanghai city - China
Tel. +86 180 1755 7329
velpchina@velp.com